



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Bona**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Bona Care Oil](#)

Bona Care Oil

Technical data sheet

Finishing



Bona Care Oil is a rapid drying maintenance oil for previously oiled wooden floors. The low viscous, unique blend of different vegetable oils, has excellent penetration ability and produces very little odour. Replenishes the pores of the wood for long-lasting protection

- Low viscosity oil with very good workability
- Low in VOC (<8%) and odour
- Safe for application on children's toys and countertops, EN 71-3 compliant

Technical data

Product base:	Modified vegetable oils
VOC:	<8%
Dilution:	Do not dilute
Drying time:	Minimum 12 hours* <i>*under normal indoor conditions, 20 °C/60% R.H. Ensure proper ventilation.</i>
Application tool:	Bona WoolPad or cotton cloth
Consumption:	50-100 m ² depending on condition of floor
Safety:	Unclassified
Fire risk:	Non flammable. Risk of self ignition, see safety data sheet for more information.
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	2 years, from the date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Sizes:	1 & 5 litre

Preparations

If necessary, the previously oiled surface must be thoroughly cleaned using Bona Soap or the Bona Deep Clean System and allowed to dry before applying maintenance oil. Allow product to reach room temperature and shake the container thoroughly before use. **Minimum temperature for use is 16°C.**

Application

1. Distribute the oil thinly with a Bona WoolPad or cotton cloth fitted under a buffing machine.
2. Remove surplus oil with cotton cloths and let dry

WARNING: BONA CARE OIL CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, RAGS, WOOL PADS AND SIMILAR MATERIAL SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS.

Maintenance

Bona[®]

Bona Care Oil

Technical data sheet

Finishing



Clean the floor regularly using a dry mop and/or a vacuum cleaner. When needed, wipe off with a damp mop with Bona Soap added to the cleaning water. Always clean using as dry a method as possible. Apply Bona Care Oil frequently to ensure that the pores of the wood remain saturated and unable to pick up dirt and moisture. The frequency of this operation is determined by the level of wear and may range from every 3rd year in a domestic environment to a few times a year in a commercial environment.

Detailed maintenance instructions are available at www.bona.com

Important notes

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test or contact Bona's technical service. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

Bona[®]