



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Craig and Rose**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Craig and Rose 1829 Eggshell Paint](#)

# TECHNICAL DATA SHEET

TDS 1829 AC/EGG 12/23 V7



## VINTAGE COLOURS

### ACRYLIC EGGSHELL

<b>TYPE OF MATERIAL</b>	A water based eggshell paint based on a pure Acrylic Emulsion resin with Titanium Dioxide and other selected pigments and Extenders.		
<b>USES</b>	A hardwearing washable eggshell sheen paint for woodwork and other surfaces receiving heavy wear. Can be used internally or on exterior wood and primed metal surfaces. It is tougher and has better adhesion than vinyl silk emulsion, but without the solvent fumes of oil based eggshell paints.		
<b>COLOURS AVAILABLE</b>	110 Vintage Colours – see website and shade card		
<b>FINISH</b>	EGGSHELL		
<b>NUMBER OF COMPONENTS</b>	One	<b>MIXING RATIO</b>	N/A
<b>METHOD OF APPLICATION</b>	Brush or Roller – can be sprayed		
<b>AVAILABLE PACKS</b>	750ml, 1Ltr & 2.5Ltr		
<b>SHEEN LEVEL</b>	Approx 16 - 24 Sheen @ 60°		
<b>PRACTICAL COVERAGE PER LITRE</b>	10-12 sq M / L, (7-9 sq M / 750 ML)		
<b>WET FILM THICKNESS RANGE</b>	60 – 75 microns		
<b>DRY FILM THICKNESS RANGE</b>	20– 25 microns		
<b>FLASH POINT</b>	N/A Water based.		
<b>DRYING TIMES:</b>	<b>SURFACE</b>	1-2 Hours	
	<b>HARD</b>	2-4 Hours	
	<b>OVERCOATING</b>	4 Hours	
<b>APPLICATION INSTRUCTIONS</b>	<p>Apply 2 coats by brush or roller (synthetic bristle brushes give good results). Previously painted gloss or lustre surfaces should be abraded to improve adhesion. See can for further details.</p> <p>Bare wood or plaster surfaces should be primed with Craig &amp; Rose Primer Undercoat for best results.</p> <p>Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood or metal as they may contain harmful lead. For further advice, please contact the British Coatings Federation Ltd, James House, Bridge Street, Leatherhead. KT22 7EP.</p>		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

## VINTAGE COLOURS

### ACRYLIC EGGSHELL

<b>RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS</b>	Ensure the previous coat is completely dry before over coating. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze.
<b>CLEANING</b>	Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water.
<b>SAFETY PRECAUTIONS</b>	Ensure good ventilation during application and drying. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full instructions. Safety Data Sheets are available on request.
<b>VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)</b>	2004/42 EU Limit value for this product ( Cat A/a :30 g/L) This product contains Max : 1.5g/L VOC.
<b>DISPOSAL &amp; ENVIRONMENT</b>	Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.