



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Liberon Garden ColourCare Decking Paint](#)



## Garden ColourCare Decking Paint

**5 YEAR**  
GUARANTEE



- Available in 5 colours
- 2 in1- Decorates and protects
- Matt opaque finish – Ideal for old and worn decking
- Washable and anti-slip\*
- Available in 2.5 litres



### Product use

Garden Colour Care Decking Paint is a 2 in 1 solution to provide a protective and decorative matt opaque finish that is ideal for old and worn decking. It is washable and anti-slip with a 5 year guarantee and will give your old decking a new lease on life.

### Preparation

To ensure a perfect finish on timber previously treated with Sealer/Paint/Woodstain, please sand and stain the existing treatment to expose the bare wood. Ensure the wood is dust-free.

- One final check: 'The Water Drop Test'. Place a small amount of water on the timber. If the water droplet absorbs into the timber, it is ok to apply the Decking Paint. If the water droplet remains on the timber surface, the Decking Paint will not adhere. Degrease the surface with denatured alcohol. .
- On new timber, wait three months before applying Decking Paint; this will then allow the timber to absorb the Decking Paint fully. On exotic, hardwood or oily timber: Please remove any excess oil.



## Application

Ideal application conditions: between 12° and 25°C, in dry weather. We wouldn't recommend applying the Decking Paint in strong winds and when bad weather is forecast. Stir the product well before and during use.

- Stir the paint with a mixer or wide stick, working around the bottom of the tin to mix it well.
- Apply the product with a brush between the grooves and edges in 2 m<sup>2</sup> areas at a time, then paint with the roller in various directions, (top to bottom and sideways), avoiding excessive application.
- Please allow 8 hours before applying a second coat. On highly porous or highly exposed decking, a third coat may be required. Ideally, allow a further 48 hours before light usage on the decking.
- If there are any signs of heavy wear or surface damage, we would advise that a maintenance coat is applied. Woods with little absorption (Iroko, Wenge, Larch etc) require a regular application of a maintenance coat.
- Applying further coats of Decking Paint: Wash existing timber with pressure washer and remove any foliage / moss and excess oil stains

## 5 Year Guarantee

5 year guarantee when the product is applied according to preparation and application instructions. On surfaces not subject to capillary rise.

## Anti-Slip

Class PN12 according to standard FNOR XP PO5-011, anti-slip system not suitable for pool edges.

## Cleaning and maintenance

For general maintenance clean with water.

## Precautions

- Wear suitable clothing and protective gloves.
- Store Liberon Garden ColourCare Decking Paint at a temperature above 5°C. Always replace the lid otherwise the product can deteriorate.
- May not be suitable for some foreign hardwoods, test first on an inconspicuous area.

## Health and Safety

Do not allow to freeze.

EUH208: Contains hydroxyphenyl benzotriazole and benzisothiazolinone. May produce an allergic reaction.

P102: Keep out of reach of children.

P271: Use only outdoors in a well-ventilated area.

P501: Dispose of contents/container to a waste collection centre. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.



**VOC information**

EU limit for this product (CatA/f): 140 g/L (2010)

This product contains max 6g/L VOC.

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical advice please contact us on 01797 367555.

Liberon Limited  
Mountfield Industrial Estate  
New Romney  
Kent  
TN28 8XU  
Tel: 01797 367555  
Fax: 01797 367575  
[www.liberon.co.uk](http://www.liberon.co.uk)

Liberon Ltd is a V33 Group Company.