



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Morrells Opaque H.C. Free Pre-Catalyst Primer](#)

Product Data Sheet



9005/519 High Build Precatalyst Primer & Pigmented Precatalyst Primers

| Code | Description | Code | Description |
|----------|-------------------|----------|-------------|
| 9005/519 | High Build Primer | Thinners | 2007/900 |

| | |
|------------------------------|---|
| Technical Data | A high build, high opacity white Precatalyst Primer specifically formulated for use on all kinds of substrate including MDF. Due to the nature of the solvents utilised this product will not encourage the dissolution of waxes at the MDF surface. Ideal for use as a base for our Fastmatch Range of pigmented Precatalyst topcoats. |
| Properties | Has a high filling and hiding power and sands/flours easily to produce a smooth surface for subsequent pigmented topcoats. Care should be taken to avoid pooling or bridging when applying to raised profiles or rebates, as this may lead to cracking. |
| Mixing Guidelines | Supplied ready for use (RFU) but can be thinned upto 5% by volume with the recommended thinner, 2007/900, if required. |
| Typical Handling | Touch Dry: 8 – 10 minutes @ 18°C Sandable: 30 minutes @ 18°C. Use 240 Silicone Carbide paper. Recoatible: 30 minutes minimum @ 18°C Packing Time: Overnight minimum, dependent on conditions. |
| Cleaning | 2007/100 should be used for cleaning equipment. |
| Coverage | Approximately 40m ² per 5Lts dependent upon the size, orientation and surface quality of the item being coated. |
| Tinting | Bespoke colours (pastels and mid-shades) can be requested from our Fastmatch Department to compliment our huge range of pigmented topcoats. |
| System Guidelines | Morrells recommends the following guidance for of use this product: Typical Finish: 1-2 coats at 95g/m ² per coat (Dry Film Thickness ~ 40µ per coat), over coated with Morrells White Precatalyst Lacquers or Morrells Fastmatch Precatalyst Lacquers. Using these products in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish. |
| Important Information | ➤ Designed for spray application. |



| | |
|-----------------------------------|---|
| | <ul style="list-style-type: none"> ➤ Leave adequate time between coats. Do not apply more than 3 coats in one day. Denib between coats to aid adhesion. ➤ Excessive coating weights can lead to cracking or lifting. ➤ Do not overcoat with 1K or 2K Polyurethane (PU) products. ➤ This product is not suitable for 'pulling over'. ➤ Use only the recommended thinner. Use of non-recommended thinner can cause uneven/patchy drying. ➤ Use 2007/200 Anti-Chill Thinners when applying in conditions of high atmospheric humidity, using a maximum of 5% by volume. ➤ Use 2007/201 Retarder Thinners to slow down the drying in warm conditions, using a maximum of 5% by volume. ➤ Product should be stored above 5°C and protected from frost. ➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. ➤ Finished products should not be subjected to environments with temperatures of < 2°C. ➤ Out of scope with 2004/42/EC. |
| <p>Health & Safety</p> | <p>Reference should be made to the appropriate MSDS for this product range, which can be found at www.morrells.co.uk</p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p> <p>This product is intended for professional use only.</p> |

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



SAFETY DATA SHEET
9005/519 HCF WHITE PRECATALYST PRIMER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 9005/519 HCF WHITE PRECATALYST PRIMER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

| | |
|---------------|---|
| Physical | Flam. Liq. 2 - H225 |
| Health | EUH066; Eye Irrit. 2 - H319; STOT Single 3 - H336 |
| Environmental | Not classified. |

Classification (1999/45) Xi; R36. F; R11. R66, R67.

Human Health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Environment

The product is not expected to be hazardous to the environment.

Physical And Chemical Hazards

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

2.2. Label elements

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

9005/519 HCF WHITE PRECATALYST PRIMER

Precautionary Statements

| | |
|--------------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P313 | Get medical advice/attention. |
| P370+378 | In case of fire: Use ... for extinction. |

Supplementary Precautionary Statements

| | |
|--------------|--|
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting/.../equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash ... thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P337 | If eye irritation persists: |
| P403+233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to ... |

Supplemental Label Information

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | |
|---|--|
| ACETONE | 5-10% |
| CAS-No.: 67-64-1 | EC No.: 200-662-2 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336 | Classification (67/548) F;R11 Xi;R36 R66 R67 |
| ETHANOL | 10-30% |
| CAS-No.: 64-17-5 | EC No.: 200-578-6 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 | Classification (67/548) F;R11 |
| ISOBUTYL ACETATE | 10-30% |
| CAS-No.: 110-19-0 | EC No.: 203-745-1 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 | Classification (67/548) F;R11 R66 |

9005/519 HCF WHITE PRECATALYST PRIMER

| | | |
|---|--|----------------|
| METHANOL | | < 1% |
| CAS-No.: 67-56-1 | EC No.: 200-659-6 | |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370 | Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25 | |
| PROPAN-1-OL | | 5-10% |
| CAS-No.: 71-23-8 | EC No.: 200-746-9 | |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336 | Classification (67/548) F;R11 Xi;R41 R67 | |
| XYLENE | | 5-10% |
| CAS-No.: 1330-20-7 | EC No.: 215-535-7 | |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 | Classification (67/548) R10 Xn;R20/21 Xi;R38 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

Composition Comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

Inhalation.

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

Skin Contact

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Use: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

9005/519 HCF WHITE PRECATALYST PRIMER

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

Specific Hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control.

Protective Measures In Fire

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge onto the ground or into water courses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|------------------|-----|-------------|----------------------------|---------------|----------------------------|-------|
| ACETONE | WEL | 500 ppm | 1210 mg/m ³ | 1500 ppm | 3620 mg/m ³ | |
| ETHANOL | WEL | 1000 ppm | 1920 mg/m ³ | | | |
| ISOBUTYL ACETATE | WEL | 150 ppm | 724 mg/m ³ | 187 ppm | 903 mg/m ³ | |
| METHANOL | WEL | 200 ppm | 266 mg/m ³ | 250 ppm | 333 mg/m ³ | |
| PROPAN-1-OL | WEL | 200 ppm(Sk) | 500 mg/m ³ (Sk) | 250 ppm(Sk) | 625 mg/m ³ (Sk) | |
| XYLENE | WEL | 50 ppm(Sk) | 220 mg/m ³ (Sk) | 100 ppm(Sk) | 441 mg/m ³ (Sk) | |

WEL = Workplace Exposure Limit.

Ingredient Comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

8.2. Exposure controls

Protective Equipment

9005/519 HCF WHITE PRECATALYST PRIMER



Process Conditions

Provide eyewash station.

Engineering Measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Hand Protection

Protective gloves and goggles must be used if there is a risk of direct contact or splash.

Eye Protection

Contact lenses should not be worn when working with this chemical! Wear approved safety goggles.

Other Protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

Hygiene Measures

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--|-------------------|
| Appearance | Liquid |
| Colour | White / off-white |
| Initial Boiling Point and Boiling Range: | 90 |
| Flash Point (°C) | 8 |

9.2. Other information

| | |
|---------------------------------|-------------|
| Volatile Organic Compound (VOC) | 587 g/litre |
|---------------------------------|-------------|

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Ingestion.

Gastrointestinal symptoms, including upset stomach.

Skin Contact

Repeated exposure may cause skin dryness or cracking.

Eye Contact

Irritating and may cause redness and pain.

SECTION 12: ECOLOGICAL INFORMATION

9005/519 HCF WHITE PRECATALYST PRIMER

Ecotoxicity:

The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point. Make sure containers are empty before discarding (explosion risk).

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code 3YE

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

9005/519 HCF WHITE PRECATALYST PRIMER

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations.

Guidance Notes

Spraying of Highly Flammable Liquids EH9. Introduction to Local Exhaust Ventilation HS(G)37.

National Regulations

Workplace Exposure Limits 2005 (EH40)

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date 15/09/2015

Revision 2

Supersedes Date 01/02/2012

Risk Phrases In Full

R10 Flammable.

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R41 Risk of serious damage to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs <<Organs>>.

SAFETY DATA SHEET
2007/900 HCF CELLULOSE THINNERS

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 2007/900 HCF CELLULOSE THINNERS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

| | |
|---------------|-----------------------------|
| Physical | Flam. Liq. 2 - H225 |
| Health | EUH066;STOT Single 3 - H336 |
| Environmental | Not classified. |

Classification (1999/45) F;R11. R66, R67.

2.2. Label elements

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H336 | May cause drowsiness or dizziness. |

Precautionary Statements

| | |
|------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P501 | Dispose of contents/container to ... |

Supplementary Precautionary Statements

| | |
|------|--|
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |

2007/900 HCF CELLULOSE THINNERS

| | |
|--------------|--|
| P241 | Use explosion-proof electrical/ventilating/lighting/.../equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P370+378 | In case of fire: Use ... for extinction. |
| P403+233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

Supplemental Label Information

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | |
|---|--|
| BUTYL ACETATE -norm | 10-30% |
| CAS-No.: 123-86-4 | EC No.: 204-658-1 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336 | Classification (67/548) R10 R66 R67 |
| ETHANOL | 30-60% |
| CAS-No.: 64-17-5 | EC No.: 200-578-6 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 | Classification (67/548) F;R11 |
| ISOBUTYL ACETATE | 10-30% |
| CAS-No.: 110-19-0 | EC No.: 203-745-1 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 | Classification (67/548) F;R11 R66 |
| METHANOL | 1-5% |
| CAS-No.: 67-56-1 | EC No.: 200-659-6 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370 | Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25 |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

2007/900 HCF CELLULOSE THINNERS

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|---------------------|-----|-------------|------------|---------------|-----------|-------|
| | | | | | | |
| BUTYL ACETATE -norm | WEL | 150 ppm | 724 mg/m3 | 200 ppm | 966 mg/m3 | |
| ETHANOL | WEL | 1000 ppm | 1920 mg/m3 | | | |
| ISOBUTYL ACETATE | WEL | 150 ppm | 724 mg/m3 | 187 ppm | 903 mg/m3 | |
| METHANOL | WEL | 200 ppm | 266 mg/m3 | 250 ppm | 333 mg/m3 | |

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment



Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--|----------------|
| Appearance | Liquid |
| Odour | Characteristic |
| Initial Boiling Point and Boiling Range: | 104 |
| Flash Point (°C) | 17 |

9.2. Other information

Volatile Organic Compound (VOC) 827 g/litre

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****General Information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity:**

There are no data on the ecotoxicity of this product.

12.1. Toxicity**12.2. Persistence and degradability****12.3. Bioaccumulative potential****12.4. Mobility in soil****12.5. Results of PBT and vPvB assessment****12.6. Other adverse effects****SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels

2007/900 HCF CELLULOSE THINNERS



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. Spraying of Highly Flammable Liquids EH9.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date 28/06/2013

Revision 2

Supersedes Date 23/06/2011

Risk Phrases In Full

R10 Flammable.

R11 Highly flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs <<Organs>>.

SAFETY DATA SHEET
2007/100 gun cleaner

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 2007/100 gun cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

| | |
|---------------|---|
| Physical | Flam. Liq. 2 - H225 |
| Health | Acute Tox. 4 - H302; Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Repr. 2 - H361d; STOT Single 2 - H371; STOT Rep. 2 - H373; Asp. Tox. 1 - H304 |
| Environmental | Not classified. |

Classification (1999/45) Xn; R20/21/22, R68/20/21/22, R48/20, R65. Repr. Cat. 3; R63. Xi; R36/38. F; R11.

2.2. Label elements

Contains: METHANOL
TOLUENE

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

| | |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |

2007/100 gun cleaner

| | |
|-------|--|
| H361d | Suspected of damaging the unborn child. |
| H371 | May cause damage to organs . |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Precautionary Statements

| | |
|--------------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P313 | Get medical advice/attention. |

Supplementary Precautionary Statements

| | |
|--------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting/.../equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash ... thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P301+312 | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P308+313 | IF exposed or concerned: Get medical advice/attention. |
| P309+311 | IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P314 | Get medical advice/attention if you feel unwell. |
| P321 | Specific treatment (see ... on this label). |
| P322 | Specific measures (see ... on this label). |
| P330 | Rinse mouth. |
| P331 | Do NOT induce vomiting. |
| P332+313 | If skin irritation occurs: Get medical advice/attention. |
| P337 | If eye irritation persists: |
| P362 | Take off contaminated clothing and wash before reuse. |
| P363 | Wash contaminated clothing before reuse. |
| P370+378 | In case of fire: Use ... for extinction. |
| P403+235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to ... |

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

2007/100 gun cleaner

| | | |
|---|---|--------------------------|
| ACETONE | | 30-60% |
| CAS-No.: 67-64-1 | | EC No.: 200-662-2 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336 | Classification (67/548) F;R11 Xi;R36 R66 R67 | |
| BUTYL ACETATE -norm | | 10-30% |
| CAS-No.: 123-86-4 | | EC No.: 204-658-1 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336 | Classification (67/548) R10 R66 R67 | |
| METHANOL | | 5-10% |
| CAS-No.: 67-56-1 | | EC No.: 200-659-6 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370 | Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25 | |
| TOLUENE | | 30-60% |
| CAS-No.: 108-88-3 | | EC No.: 203-625-9 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304 | Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|---------------------|-----|-------------|---------------|---------------|---------------|-------|
| ACETONE | WEL | 500 ppm | 1210 mg/m3 | 1500 ppm | 3620 mg/m3 | |
| BUTYL ACETATE -norm | WEL | 150 ppm | 724 mg/m3 | 200 ppm | 966 mg/m3 | |
| METHANOL | WEL | 200 ppm | 266 mg/m3 | 250 ppm | 333 mg/m3 | |
| TOLUENE | WEL | 50 ppm(Sk) | 191 mg/m3(Sk) | 150 ppm(Sk) | 574 mg/m3(Sk) | |

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment



2007/100 gun cleaner

Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--|----------------|
| Appearance | Liquid |
| Odour | Characteristic |
| Initial Boiling Point and Boiling Range: | 92 |
| Flash Point (°C) | -1 |

9.2. Other information

| | |
|---------------------------------|-------------|
| Volatile Organic Compound (VOC) | 838 g/litre |
|---------------------------------|-------------|

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General Information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

2007/100 gun cleaner

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

There are no data on the ecotoxicity of this product.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

2007/100 gun cleaner

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date 28/06/2013

Revision 2

Supersedes Date 23/06/2011

Risk Phrases In Full

R10 Flammable.

R11 Highly flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs <<Organs>>.

H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.