



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Prestonett**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Prestonett Multi Purpose Interior Filler](#)

INTERIOR MULTIPURPOSE FILLER



PRODUCT ADVANTAGES

- + One product for different jobs
- + Fills up to 5 cm in 1 application
- + Easy to mix
- + Easy to apply
- + Easy to sand
- + No flashing or grinning
- + Brilliant white

GENERAL INFORMATION

Description

Powder multipurpose filler

Intended use

- Interior
- Filling holes and cracks
 - Levelling and finishing surfaces
 - Taping and jointing plasterboards
 - Coving adhesive




USE

DILUTION	50% - i.e. 0.50 litre of water per 1 kg of powder
PREPARATION	Gradually pour the powder into water, stirring until a homogeneous paste is obtained.
APPLICATION	
<i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
<i>Equipment</i>	Filling knife, blade, smoothing trowel.
<i>Operational mode</i>	Jointing : fill the joint and embed the tape and then cover with product to fully fill the tapered edge board and feather out onto the board. Once dry sand to a smooth surface and apply a second coat feathering out further than the first.
<i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
APPLICATION THICKNESS	5 cm
AVERAGE CONSUMPTION	1 kg of powder fills a volume of 1 litre
SUBSTRATES	Concrete, cellular concrete, cement, concrete block, brick, mortars, plaster, plasterboard, stone, glass cloth, old painted substrates. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
OVERCOAT	Primer, interior conventional paint, light-weight wall coverings.

INTERIOR MULTIPURPOSE FILLER



TECHNICAL DATA

COMPONANTS	Plaster base coat mix, organic binder, mineral fillers, additives.
pH	Neutral
COLOUR	White
WORKING TIME AT 20°C	60 minutes
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 3
NORM	NF EN 13 963 - class 4b
V.O.C	< 0.5 g/l (Ready mixed)
HEALTH AND SAFETY	 <p>Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com</p>
PACKAGING	2 kg , 1 kg box - 15 kg, 5 kg bag
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.