



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Prestonett**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Prestonett Ready Mixed Interior and Exterior Filler](#)

INT/EXT READY MIXED FILLER



GENERAL INFORMATION

Description

Ready mixed filler

Intended use

Interior/exterior

- Filling small holes and cracks

Use



interior/
exterior

Application
thickness



1 cm

Working
time



Unlimited

Dilution



Ready
mixed

Manual
application



PRODUCT ADVANTAGES

- + Excellent adhesion to substrates
- + Easy to apply
- + Dries hard
- + Easy to sand
- + Odourless

USE

DILUTION

Ready mixed

APPLICATION

- *Conditions*

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

- *Equipment*

Filling knife, blade, smoothing trowel.

- *Equipment cleaning*

With water before completely dry.
Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS

1 cm

AVERAGE CONSUMPTION

0.5 kg/m²

SUBSTRATES

Concrete, cement, brick, concrete block, old painted substrates, plaster, plasterboard.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.


OVERCOAT

Primer, interior conventional paint, light-weight wall coverings, fibreglass cloth.



INT/EXT READY MIXED FILLER

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1.7 ± 0.1
pH	8 ± 1
COLOUR	White
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36 005 Family III – class 2
NORM	NF EN 16566
V.O.C	< 20 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	1 kg bucket
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.