

The following Product Datasheet is provided by **Starcke**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Starcke (Ersta) 9 Hole 125mm Aluminium Oxide Velcro Backed Sanding Discs



Product Information

| Base Stock | Flexible latex B- and C- weight paper with high tear resistance |
|----------------------------|---|
| Bonding | Resin over resin with dust-repellent additives in the top coat |
| Grain Type | Aluminium oxide |
| Coating | Semi open coat |
| Grain Size | 542 B7 : P 800 - P 150 542 C7 : P 120 - P 60, P 40 |
| Manufactured Width | 1650 mm |
| Availability | Sheets, cut sheets, discs, velcro discs, rolls |
| | primer and subsequent paint finish. Deburring and roughing of plastic parts such as: Bumpers, door mouldings and ornamental edgings. High finish quality for paint jobs. Woodworking. |
| Advantages | Full resinoid bonding ensures excellent performance and durability. Also suitable for brief damp sanding applications. The dust-repellent additive incorporated as top coat prevents premature clogging of the grain surface. Unlike conventional stearate coating this repellent effect is maintained throughout the product life. Brown aluminium oxide grain for maximum performance and durability. Designed to eliminate file marks on vehicle structures. A product with universal application possibilities, thus resulting in an econominal stock keeping. |
| Metal Car Paint Shop | Wood Floor Sanding Paint Lacquer Filler China Ceramics Leather Glass Plastics Stone |

STARCKE GmbH & Co. KG

Markt 10 | 49324 Melle, Germany

Phone +49 (0) 5422 966-0
Telefax +49 (0) 5422 966-444
E-Mail info@starcke.de
Internet www.starcke.de