

The following Product Datasheet is provided by Starcke

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Starcke (Ersta) 93mm x 14m Aluminium Oxide Roll

ERSTA



## **Product Information**

## Article No. 542 B7 and 542 C7 Aluminium Oxide Paper

Base Stock	Flexible latex B- and C- weight paper with high tear resistance	
Bonding	Resin over resin with dust-repellent additives in the top coat	
Grain Type	Aluminium oxide	
Coating	Semi open coat	
Grain Size	<b>542 B7:</b> P 800 - P 150 <b>542 C7:</b> P 120 - P 60, P 40	
Manufactured Width	1650 mm	
Availability	Sheets, cut sheets, discs, velcro discs, rolls	
Market Segment	<ul> <li>Automotive industry - vehicle manufacture and repair. Dry sanding of electrocoat, primer and subsequent paint finish. Deburring and roughing of plastic parts such as:</li> <li>Bumpers, door mouldings and ornamental edgings.</li> <li>High finish quality for paint jobs.</li> <li>Woodworking.</li> </ul>	
Advantages	<ul> <li>Full resinoid bonding ensures excellent performance and durability. Also suitable for brief damp sanding applications.</li> <li>The dust-repellent additive incorporated as top coat prevents premature clogging of the grain surface. Unlike conventional stearate coating this repellent effect is maintained throughout the product life.</li> <li>Brown aluminium oxide grain for maximum performance and durability. Designed to eliminate file marks on vehicle structures.</li> <li>A product with universal application possibilities, thus resulting in an econominal stock keeping.</li> </ul>	
Car Metal Paint Shop	Wood Floor SandingPaint Lacquer FillerChina CeramicsLeatherGlassPlasticsStone	

## STARCKE GmbH & Co. KG

Markt 10 | 49324 Melle, Germany

Phone	+49 (0) 5422 966-0
Telefax	+49 (0) 5422 966-444
E-Mail	info@starcke.de
Internet	www.starcke.de