

The following Safety Datasheet is provided by Zinsser

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Zinsser B-I-N Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830



SAFETY DATA SHEET

Zinsser BIN® Primer-Sealer Stain-Killer

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

- Product name
- : Zinsser BIN® Primer-Sealer Stain-Killer

Product description

: Paint. Primer

Product type

: Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Industrial uses Consumer uses Professional uses				
Uses advised against	Reason			
None identified.	-			

1.3 Details of the supplier of the safety data sheet

Rust-Oleum Europe - Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium Telephone no.: +32 (0) 13 460 200 Fax no.: +32 (0) 13 460 201

e-mail address of person : rpmeurohas@ro-m.com responsible for this SDS

1.4 Emergency telephone number

Supplier	
Telephone number	: +44 (0) 207 858 1228
Hours of operation	: 24/7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



SECTION 2: Hazards identification

Hazard statements	Cause	flammable liquid and vapour. s serious eye damage. ause an allergic skin reaction.
Precautionary statements		
General	P103 -	Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.
Prevention	P233 - P280 -	Keep away from heat, sparks and hot surfaces No smoking. Keep container tightly closed. Wear protective gloves and eye/face protection: I rubber gloves. safety glasses with side-shields.
Response	P305 - P351 - P338 - P370 -	Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of fire: Use water spray, dry chemical powder or carbon dioxide for extinction.
Storage		Store in a well-ventilated place. Keep cool.
Disposal		Dispose of contents and container in accordance with all local, regional, al and international regulations.
Hazardous ingredients	Resin	acids and Rosin acids, fumarated, esters with glycerol
Supplemental label elements	Not ap	plicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not ap	plicable.
Special packaging requirem	<u>nts</u>	
Containers to be fitted with child-resistant fastenings	Not ap	plicable.
Tactile warning of danger	Yes, a	pplicable.
2.3 Other hazards		

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture			
Product/ingredient	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
name				
ethanol	EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥25 - ≤50	Flam. Liq. 2, H225	[2]
Resin acids and Rosin acids, fumarated, esters with glycerol	EC: 307-051-0 CAS: 97489-11-7	≤10	Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

2/14

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid m	eas	ures
General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	-	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	-	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Resin acids and Rosin acids, fumarated, esters with glycerol. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

SECTION 4: First aid measures

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any im	mediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures		
5.1 Extinguishing media		
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.	
Unsuitable extinguishing media	: Do not use water jet.	
5.2 Special hazards arising f	rom the substance or mixture	
Hazards from the substance or mixture	: Highly flammable liquid and vapour. Vapour may cause flash fire. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Not available.	
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. 	
Additional information	: Take precautionary measures against electrostatic discharges.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.4 Dressutions for sofe	Drevent the creation of flowmaking an evaluative concentrations of venerus in size and
7.1 Precautions for safe handling	 Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring
	from one container to another.
	Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
	Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
	Put on appropriate personal protective equipment (see Section 8).
	Never use pressure to empty. Container is not a pressure vessel.
	Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.
	Do not allow to enter drains or watercourses.
	Information on fire and explosion protection
	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Do not store above the following temperature: 30°C (86°F). Store in a dry, cool and wellventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds (in tonnes)

Danger criteria

	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000

7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient	name	Exposure limit values					
ethanol		EH40/2005 WELs (Un TWA: 1920 mg/m³ 8 l TWA: 1000 ppm 8 ho		2011).			
Recommended monitoring : procedures	atmosphere or l of the ventilation protective equip the following: E the assessment limit values and atmospheres - (of exposure to o (Workplace atm for the measure	biological monitoring man or other control measurement. Reference shou suropean Standard EN 6 to f exposure by inhalati measurement strategy Guide for the application chemical and biological tospheres - General requirement of chemical agent	exposure limits, persona ay be required to determ ures and/or the necessity d be made to monitoring 89 (Workplace atmosph on to chemical agents for bear agents of procedures agents) European Standard En and use of procedures agents) European Stand uirements for the perform s) Reference to national nation of hazardous sub	ine the eff / to use re- g standard heres - Gu or compar N 14042 (for the as dard EN 4 mance of al guidanc	fectivene espirator ds, such uidance rison with Workpla ssessme 482 procedu re	ry for h ace ent ures	
DNELs/DMELs	•						
No DNELs/DMELs available.							
PNECs							
No PNECs available							
8.2 Exposure controls							
Appropriate engineering : controls	achieved by the these are not su	use of local exhaust ve ufficient to maintain con	asonably practicable, thi ntilation and good gener centrations of particulate atory protection must be	ral extract	tion. If		
Date of issue/Date of revision	: 6/12/2017 D a	te of previous issue	: 6/12/2017	Version	: 3	6/14	

SECTION 8: Exposure controls/personal protection

Individual protection meas	sures	
Hygiene measures		Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection		Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: safety glasses with side-shields .

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. . ..

...

Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber (0.6 mm), fluor rubber foil or PTFE (EN 374).
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source:
	EN 374-3 : 2003
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type AX) (EN 140).
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

. .

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	9.1 Information on basic physical and chemical properties				
<u>Appearance</u>					
Physical state	:	Liquid. [Viscous liquid.]			
Colour	:	White.			
Odour	:	Alcohol-like.			
Odour threshold	:	Not available.			
рН	:	4,5			
Melting point/freezing point	:	Not available.			
Initial boiling point and boiling range	:	78°C			
Flash point	:	Closed cup: 17°C [Setaflash.]			
Evaporation rate	:	<1 (Butyl acetate. = 1)			
Flammability (solid, gas)	:	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Flammable in the presence of the following materials or conditions: heat. Vapour may travel a considerable distance to source of ignition and flash back. Emits toxic fumes when heated to decomposition.			
Upper/lower flammability or explosive limits	:	Lower: 3% Upper: 19%			
Vapour pressure	:	10 kPa [room temperature]			
Vapour density	:	>1 [Air = 1]			
Relative density	:	1,22 to 1,24			
Solubility(ies)	:	Easily soluble in the following materials: methanol. Partially soluble in the following materials: acetone. Very slightly soluble in the following materials: cold water and hot water. Insoluble in the following materials: diethyl ether and n-octanol.			
Partition coefficient: n-octanol/ water	:	Not available.			
Auto-ignition temperature	:	180°C			
Decomposition temperature	:	>200°C			
Viscosity	:	Dynamic (room temperature): >500 mPa⋅s Kinematic (room temperature): >4,03 cm²/s			
Explosive properties	:	Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge. Slightly explosive in the presence of the following materials or conditions: heat. Take precautionary measures against electrostatic discharges.			
Oxidising properties	:	Not available.			

9.2 Other information

No additional information.

SECTION 10: Stabil	 Iity and reactivity No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Date of issue/Date of revision	: 6/12/2017 Date of previous issue : 6/12/2017 Version : 3 8/14

SECTION 10: Stability and reactivity

10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Conclusion/Summary Acute toxicity estimates Not available.	: Not available.
Irritation/Corrosion	
Conclusion/Summary	
Skin	: Based on available data, the classification criteria are not met.
Eyes	: Causes serious eye damage.
Respiratory	: Based on available data, the classification criteria are not met.
Sensitisation	
Conclusion/Summary	
Skin	: May cause an allergic skin reaction.
Respiratory	: Based on available data, the classification criteria are not met.
Mutagenicity	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
<u>Teratogenicity</u>	
Conclusion/Summary	Not available.
Specific target organ toxicit	<u>y (single exposure)</u>
Not available.	
Specific target organ toxicit	<u>y (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
	te en unelling allemente affende finans allement and lanes demonstrations
	ts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects

SECTION 11: Toxicological information

Conclusion/Summary	: Not available.
General	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Volatile.
12.5 Results of PBT and	vPvB assessment
PBT	: Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

<u>Product</u> Methods of disposal	Dispo with th and a recyc dispo	sal o e ree ny re able sed o	ation of waste should be f this product, solutions quirements of environma gional local authority red products via a licensed of untreated to the sewer ies with jurisdiction.	and any by-products ental protection and v quirements. Dispose waste disposal contra	should at all tim waste disposal le of surplus and l actor. Waste sh	es co egisla non- iould i	tion not be
Hazardous waste	: Yes.						
Date of issue/Date of revision	: 6/12	2017	Date of previous issue	: 6/12/2017	Version	:3	10/14

SECTION 13: Disposal considerations

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	1263	1263	1263	1263
14.2 UN proper shipping name	Paint.	Paint.	Paint.	Paint.
14.3 Transport hazard class(es)		3	3	3
14.4 Packing group	II	11	11	11
14.5 Environmental hazards	No.	No.	No.	No.
Additional information Remarks: (≤ 5L:) Limited Quantity - ADR/IMDG 3.4 ADR Tunnel code: (D/ E)		-	Emergency schedules (EmS): F-E + <u>S-E</u> Marine pollutant: NO Remarks: (≤ 5L:) Limited Quantity - ADR/IMDG 3.4.6	Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 353 Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 364 Limited Quantities - Passenger Aircraft

SECTION 14: Transport information		
		Quantity limitation: 1 L Packaging instructions: Y 341

^{14.6} Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

•	-
	onmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 190	
	nces subject to authorisation
Annex XIV	
None of the components a	
Substances of very high	
None of the components a	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: IIA/i. One-pack performance coatings. EU limit value for this product : 500g/l (2010.) This product contains a maximum of 500 g/l VOC.
Europe inventory	: All components are listed or exempted.
Ozone depleting substand	:es (1005/2009/EU)
Not listed.	
Prior Informed Consent (P Not listed.	<u>IC) (649/2012/EU)</u>
Seveso Directive This product is controlled ur	ider the Seveso Directive.
Danger criteria	
Category	
P5c: Flammable liquids 2	and 3 not falling under P5a or P5b
	The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
References	: EH40/2005 Workplace exposure limits Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830
International regulations	
Chemical Weapon Convent	ion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol (Annexes	<u>s A, B, C, E)</u>
Not listed.	
Date of issue/Date of revision	: 6/12/2017 Date of previous issue : 6/12/2017 Version : 3 12/14
·	

SECTION 15: Regulatory information Stockholm Convention on Persistent Organic Pollutants Not listed. **Rotterdam Convention on Prior Informed Consent (PIC)** Not listed. **UNECE Aarhus Protocol on POPs and Heavy Metals** Not listed. **CN** code : 3208 90 99 **UFI Code** : 5GTS-H8KV-1XEC-890H **International lists National inventory Australia** : Not determined. Canada : Not determined. China : Not determined. : Japan inventory (ENCS): Not determined. Japan Japan inventory (ISHL): Not determined. Malaysia : Not determined. **New Zealand** : Not determined. **Philippines** : Not determined. **Republic of Korea** : Not determined. : Not determined. Taiwan : Not determined. **Turkey United States** : Not determined. **15.2 Chemical safety** : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information	that has changed	from previously is	sued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Eye Dam. 1, H318	Expert judgment Expert judgment Expert judgment	

Full text of H-phrases referred to in sections 2 and 3

Full text of abbreviated H : statements	H317	Highly flammable liquid and vapour. May cause an allergic skin reaction.
	H318	Causes serious eye damage.

SECTION 16: Other information

Full text of classifications [CLP/GHS]	:		SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 2 SKIN SENSITISATION - Category 1
Date of printing	:	4/01/2018	
Date of issue/ Date of revision	:	6/12/2017	
Date of previous issue	1	6/12/2017	
Version	:	3	
· · · · · ·			

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.